

# DARRANT CHEMICALS

## SAFETY DATA SHEET ACETONE

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	ACETONE
Product number	586
Synonyms; trade names	DIMETHYL KETONE,DMK,2- PROPANONE,PROPAN-2-ONE,ACETONE MIN 99.5%,ACETONE PH,ACETONE HIGH PURITY,MX-THINNERS HTS 10208,ACETONE HP,MX-THINNER HTS 10268,ACETONE INDUSTRIAL,ACETONE PHARMA GRADE,ACETONE – HÖGANÄS,ACETONE PHARMA – INV. LACKADE,ACETONE PHARMA,ACETONE,ACETONE NF,ACETONE EP,ACETONE GLD,ACETONE STATOIL
REACH registration number	01-2119471330-49
CAS number	67-64-1
EU index number	606-001-00-8
EC number	200-662-2

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Lab Reagent Industrial Solvent Production of Rubber Oilfields Surface coating Chemical Intermediate Polymers Process Additive Monomer Binder Release Agent Formulation Resin. Cosmetics
-----------------	---

#### 1.3. Details of the supplier of the safety data sheet

Supplier	DARRANT CHEMICALS Unit 1 Witham Point Business Park Wavell Drive Lincoln LN3 4PL
----------	---

#### 1.4. Emergency telephone number 01522 521864

Emergency Contact Number 0207 4055375

(Outside Office Hours)

Emergency Contact Number 01522 521864  
(Office Hours)

Sds No. 586

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

Physical hazards	Flam. Liq. 2 - H225
Health hazards	Eye Irrit. 2 - H319 STOT SE 3 - H336

Revision date: 18/09/2013

Revision: 02 ACETONE

Classification (67/548/EEC or 1999/45/EC) F; R11. Xi; R36. R67

## 2.2. Label elements

EC number 200-662-2



Pictogram

Signal word Danger

Hazard statements  
 H225 Highly flammable liquid and vapour.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

Precautionary statements  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261 Avoid breathing vapour/spray.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P501 Dispose of contents/container in accordance with national regulations.

## 2.3. Other hazards

\_\_\_\_\_

This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

\_\_\_\_\_

Product name ACETONE

REACH registration number 01-2119471330-49

EU index number 606-001-00-8

CAS number 67-64-1

EC number 200-662-2

Composition comments The data shown are in accordance with the latest EC Directives.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

\_\_\_\_\_

General information Keep the affected person warm and at rest. Get prompt medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.

Ingestion Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse mouth thoroughly with water. Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

## 4.2. Most important symptoms and effects, both acute and delayed

\_\_\_\_\_

Inhalation Drowsiness, dizziness, disorientation, vertigo. Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.

Ingestion	Central nervous system depression.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat according to symptoms: No specific recommendations. If in doubt, get medical attention promptly.
----------------------	--

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours. Oxides of the following substances: Carbon. CAUTION: Reignition may occur Vapours may form explosive mixtures with air.

#### 5.3. Advice for firefighters

Protective actions during firefighting Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No smoking, sparks, flames or other sources of ignition near spillage. Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of spray mist and contact with skin and eyes. Provide adequate ventilation. Warn everybody of potential hazards and evacuate if necessary.

#### 6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Provide adequate ventilation. Contain spillage with sand, earth or other suitable noncombustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with inert, damp, non-combustible material. Flush contaminated area with plenty of water. Provide adequate ventilation. Flush contaminated area with plenty of water. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. No smoking, sparks, flames or other sources of ignition near spillage. Stop leak if possible without risk.

#### 6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

**Usage precautions** Avoid contact with skin and eyes. Provide adequate ventilation. Vapours may accumulate on the floor and in low-lying areas. Keep away from heat, sparks and open flame. Avoid the formation of mists. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Protect against direct sunlight. Mechanical ventilation or local exhaust ventilation may be required. Use explosion proof electric equipment. Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage precautions** Keep away from flammable and combustible materials. Earth container and transfer equipment to eliminate sparks from static electricity. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Suitable container materials: Stainless steel. Polyethylene-lined mild steel. Glass.

**Storage class** Flammable liquid storage.

**7.3. Specific end use(s)**

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

**SECTION 8: Exposure Controls/personal protection****8.1. Control parameters Occupational exposure limits**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

**DNEL**

- Industry - Dermal; Long term : 186 mg/kg/day
- Industry - Inhalation; Short term : 2420 mg/m<sup>3</sup>
- Industry - Inhalation; Long term : 1210 mg/m<sup>3</sup>
- Consumer - Oral; Long term : 62 mg/kg/day
- Consumer - Dermal; Long term : 62 mg/kg/day
- Consumer - Inhalation; Long term : 200 mg/m<sup>3</sup>

**PNEC**

- Fresh water; 10.6 mg/l
- Marine water; 1.06 mg/l
- water; 21 mg/l
- Sediment; 3.04 mg/kg
- Soil; 33.3 mg/l
- STP; 29.5 mg/l

**8.2. Exposure controls****Protective equipment**

**Appropriate engineering controls**

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

**Personal protection**

Wear anti-static footwear

**Eye/face protection**

The following protection should be worn: Chemical splash goggles.

**Hand protection**

It is recommended that gloves are made of the following material: Butyl rubber.

Other skin and body protection	Wear rubber apron. Wear rubber footwear.
Hygiene measures	Provide eyewash station. Wash hands after handling. Avoid contact with eyes. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type A2.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colourless.
Odour	Characteristic.
Odour threshold	47.5
pH	pH (diluted solution): 5-6 50
Melting point	-94.7°C
Initial boiling point and range	55.8 - 56.6°C @
Flash point	-17°C CC (Closed cup).
Evaporation rate	0.5 (diethyl ether = 1)
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2.5 Upper flammable/explosive limit: 14.3
Vapour pressure	24.1 kPa @ °C
Vapour density	2
Relative density	0.79 @ 20°C
Bulk density	0.79 kg/l
Solubility(ies)	Soluble in water.
Partition coefficient	: -0.24
Auto-ignition temperature	465°C
Viscosity	0.32 mPa s @ 20°C

### 9.2. Other information

Refractive index	1.358 - 1.359
Molecular weight	58.09

Volatile organic compound This product contains a maximum VOC content of 790 g/litre.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Does not decompose when used and stored as recommended.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Forms explosive mixtures with air. Avoid the following conditions: Chlorinated hydrocarbons.

### 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents. Amines. Strong reducing agents. Alkalis - inorganic. Alkalis - organic.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). products

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub>) 5,800.0  
mg/kg

Species Rat

Notes (oral LD<sub>50</sub>) OECD 401

#### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub>) 15,800.0  
mg/kg

Species Rat

#### Acute toxicity - inhalation

Acute toxicity inhalation 76.0  
(LC<sub>50</sub> vapours mg/l)

Species Rat

ATE inhalation (vapours mg/l) 76.0

**Inhalation** Drowsiness, dizziness, disorientation, vertigo. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

**Ingestion** May cause nausea, headache, dizziness and intoxication. Gastrointestinal symptoms, including upset stomach. Central nervous system depression.

**Skin contact** Irritating to skin. Repeated exposure may cause skin dryness or cracking.

**Eye contact** Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

## SECTION 12: Ecological Information

### 12.1. Toxicity

Toxicity	Not considered toxic to fish.
Acute toxicity - fish	LC50, 96 hours, 96 hours: 5540 mg/l, Onchorhynchus mykiss (Rainbow trout) LC50, 96 hours, 96 hours: > 100 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC <sub>50</sub> , 48 hours, 48 hours: 8800 mg/l, Daphnia magna
Acute toxicity microorganisms	, : 1000 mg/l, Activated sludge
12.2. Persistence and degradability	
Persistence and degradability	The product is readily biodegradable.
Biodegradation	water - Degradation (%) 91: 28 days The substance is readily biodegradable.
Chemical oxygen demand	2.21 g O <sub>2</sub> /g substance
12.3. Bioaccumulative potential	
Bioaccumulative potential	The product is not bioaccumulating. BCF: 3,
Partition coefficient	: -0.24
12.4. Mobility in soil	
Mobility	The product is soluble in water.
Adsorption/desorption coefficient	Soil - : 1.5 @ 20C°C
Henry's law constant	3311 Pa m <sup>3</sup> /mol @ 25°C assessment
12.5. Results of PBT and vPvB	
Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
12.6. Other adverse effects	
Other adverse effects	No information required.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information	Do not puncture or incinerate, even when empty. Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids. Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

General	Wear protective clothing as described in Section 8 of this safety data sheet.
14.1. UN number	
UN No. (ADR/RID)	1090
UN No. (IMDG)	1090

UN No. (ICAO) 1090

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) ACETONE

Proper shipping name (IMDG) ACETONE

Proper shipping name (ICAO) ACETONE

Proper shipping name (ADN) ACETONE 14.3.

Transport hazard class(es)

ADR/RID class 3

ADR/RID subsidiary risk

ADR/RID label 3

IMDG class 3

IMDG subsidiary risk 3

ICAO class/division

ICAO subsidiary risk

Transport labels



#### 14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

#### 14.6. Special precautions for user

EmS F-E, S-D

Emergency Action Code •2YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to required. Annex II of MARPOL 73/78 and the IBC Code No information

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). This product may impact SEVESO storage regulations.
Guidance	CHIP for everyone HSG228. Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. DSEAR
Water hazard classification	WGK 1
Inventory Information	EINECS TSCA MITI DSL
15.2. Chemical safety assessment	

A chemical safety assessment has been carried out.

#### SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	18/09/2013
Revision	02
SDS number	586
SDS status	Approved.
Signature	Jitendra Panchal
Risk phrases in full	R11 Highly flammable. R36 Irritating to eyes. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

TURKISH SIGNATURE